

Model Specifications for the 300 & 400 Pull-Types

Model 300 Pull-Type	imperial	metric	Model 400 Pull-Type	imperial	metric
- Empty Weight	5,270 lbs.	2,395 kg.	- Empty Weight	6,200 lbs.	2,818 kg.
- Height	98 in.	249 cm	- Height	102 in.	258 cm
- W/10" Extension	108 in.	274 cm	- W/10" Extension	112 in.	283 cm
- Overall Width*	97 in.	246 cm	- Overall Width*	110 in.	279 cm
- Overall Length	170 in.	432 cm	- Overall Length	178 in.	452 cm
- Min. HP Req.**	50		- Min. HP Req.**	60	
- Capacity W/10" Extension (cu. ft.)	278 cu. ft.	7.9 cu. m	- Capacity W/10" Extension	378 cu.ft.	10.7 cu.m
- Capacity Struck Level	235 cu. ft.	6.7 cu. m	- Capacity Struck Level (cu. ft.)	321 cu.ft.	9.1 cu.m

All Above Models

* Overall width as equipped with standard drop chute.

** Horsepower requirements dependent on weight and commodity mix.

Due to continuing improvements in the design and manufacturing of equipment, specifications and technical data are subject to change without incurring any obligation on goods purchased.



Models 300/400 Pull-Types

STANDARD EQUIPMENT

- Patented Freestanding Vertical Mixing Auger
- Heavy-Duty Planetary Drive
- Replaceable Cutting Blades (4)
- AR200 Steel Backing Plates
- 540 Or Optional 1000 rpm PTO (specify on order)
- Heavy-Duty Tubular Steel Frame
- 5/8" M/S Floor
- 1/2" AR200 Lower Screw Flighting
- Left or Right Hand Side Door With Drop Chute (Specify On Order) - Discharge Height 23"
- 3 point DG Electronic Scale System with Remote Port and 10 Recipe Programming Capability.
- 12 Volt Battery
- Model 300 (2) 12.5L-15, 12 Ply Rated Hwy Service Tires, Capacity 6000 lbs At Less Than 5 mph
- Model 400 (2) 19x45x17 Floatation Implement Tires Capacity 10,000 lbs At Less Than 5 mph
- Heavy Duty Hitch Jack
- Ultra Wear Kicker Plate
- Tub Mounted Hydraulic Interference Knife Assemblies (2)