

# Model Specifications for the 500 & 600 Pull-Types

<b>Model 500 Pull-Type</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight	9,016 lbs.	4,098 kg.
- Height*	103 in.	262 cm
- W/10" Extension	113 in.	287 cm
- Overall Width**	102 in.	259 cm
- Overall Length	222 in.	564 cm
- Min. HP Req.***	80	
- Capacity W/10" Extension (cu. ft.)	462 cu. ft.	13.1 cu. m
- Capacity Struck Level	398 cu. ft.	11.3 cu. M



<b>Model 600 Pull-Type</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight	9,766 lbs.	4,439 kg.
- Height*	113 in.	287 cm
- W/10" Extension	123 in.	312 cm
- Overall Width**	102 in.	259 cm
- Overall Length	225 in.	572 cm
- Min. HP Req.***	90	
- Capacity W/10" Extension	537 cu.ft.	15.2 cu.m
- Capacity Struck Level (cu. ft.)	469 cu.ft.	13.3 cu.m

## All Above Models

\* Height measured with standard 245 x 70 x 17.5 Truck Tires

\*\* Overall width and length dependent on style of conveyor/discharge and options ordered (dog-leg conveyor adds 4" of width).

\*\*\* Horsepower requirements dependent on weight and commodity mix.

*Due to continuing improvements in the design and manufacturing of equipment, specifications and technical data are subject to change without incurring any obligation on goods purchased.*

## Models 500 & 600 Pull-Types

### STANDARD EQUIPMENT

- Patented Freestanding Vertical Mixing Auger
- Heavy-Duty, Two-Stage Planetary Drive
- Replaceable Cutting Blades (5)
- AR200 Steel Backing Plates
- 540 Or Optional 1000 rpm PTO (Specify On Order)
- Heavy-Duty Tubular Steel Frame
- 3/4" M/S Floor
- 1/4" AR200 Side Walls
- 5/8" AR200 Lower Screw Flighting
- Front Center Door With 8 Ft. Flat Hydraulic
- Driven Chain Conveyor, Discharge Height 25 in., Right Or Left Discharge (Specify On Order).
- Heavy Duty Hitch Jack
- 12 Volt Battery
- Solid truck axle with (4) 245 x 70 x 17.5 Truck Tires, Payload Capacity 14000lbs at less than 5 mph.
- Ultra Wear Kicker Plate
- Tub Mounted Hydraulic Interference Knife Assemblies (2)