

Model Specifications

For the

600T, 700T, 900T, 1000T, 1200T & 1400T Pull-Types



Model 600T Pull-Type			imperial	metric	Model 1000T Pull-Type			imperial	metric
- Empty Weight	12,100 lbs.	5,500 kg.			- Empty Weight	19,400 lbs.	8,818 kg.		
- Height	104 in.	264 cm			- Height	111 in.	282 cm		
- W/10" Extension	114 in.	290 cm			- W/10" Extension	121 in.	307 cm		
- Overall Width*	102 in.	259 cm			- Overall Width*	129 in.	328 cm		
- Overall Length	253 in.	643 cm			- Overall Length	310 in.	787 cm		
- Min. HP Req.**	100				- Min. HP Req.**	170			
- Capacity W/10" Extension (cu. ft.)	641 cu. ft.	18.2 cu. m			- Capacity W/10" Extension	906 cu.ft.	25.7 cu.m		
- Capacity Struck Level	549 cu. ft.	15.5 cu. m			- Capacity Struck Level (cu. ft.)	789 cu.ft.	22.3 cu.m		
Model 700T Pull-Type			imperial	metric	Model 1200T Pull-Type			imperial	metric
- Empty Weight	12,100 lbs.	5,500 kg.			- Empty Weight	19,850 lbs.	9,023 kg.		
- Height	112 in.	284 cm			- Height	118 in.	300 cm		
- W/10" Extension	122 in.	310 cm			- W/10" Extension	128 in.	325 cm		
- Overall Width*	102 in.	259 cm			- Overall Width*	129 in.	328 cm		
- Overall Length	243 in.	617 cm			- Overall Length	313 in.	795 cm		
- Min. HP Req.**	100				- Min. HP Req.**	180			
- Capacity W/10" Extension (cu. ft.)	649 cu. ft.	18.4 cu. m			- Capacity W/10" Extension	1072 cu.ft.	30.4 cu.m		
- Capacity Struck Level	568 cu. ft.	16.1 cu. m			- Capacity Struck Level (cu. ft.)	933 cu.ft.	26.4 cu.m		
Model 900T Pull-Type			imperial	metric	Model 1400T Pull-Type			imperial	metric
- Empty Weight	16,000 lbs.	7,273 kg.			- Empty Weight	23,500 lbs.	10,682 kg.		
- Height	116 in.	295 cm			- Height	128 in.	325 cm		
- W/10" Extension	126 in.	320 cm			- W/10" Extension	138 in.	351 cm		
- Overall Width*	120 in.	305 cm			- Overall Width*	123 in.	312 cm		
- Overall Length	272 in.	691 cm			- Overall Length	328 in.	833 cm		
- Min. HP Req.**	130				- Min. HP Req.**	230			
- Capacity W/10" Extension (cu. ft.)	849 cu. ft.	24.1 cu. m			- Capacity W/10" Extension (cu. ft.)	1312 cu. ft.	37.2 cu. m		
- Capacity Struck Level	739 cu. ft.	20.9 cu. m			- Capacity Struck Level	1157 cu. ft.	32.8 cu. m		

Additional information

* Overall width and length dependent on style of conveyor / discharge and options ordered.

** Horsepower requirements dependent on weight and commodity mix.

Due to continuing improvements in the design and manufacturing of equipment, specifications and technical data are subject to change without incurring any obligation on goods purchased.

Models 600T, 700T, 900T, 1000T, 1200T & 1400T Pull-Types

STANDARD EQUIPMENT

- Two Patented Freestanding Vertical Mixing Augers
- Two Heavy-Duty, Two-Stage Planetary Drives
- Replaceable Cutting Blades (10)
- AR200 Steel Backing Plates
- 1000 Or Optional 540 rpm PTO (Specify On Order)
- Heavy-Duty Tubular Steel Frame
- 3/4" M/S Floor (1" on all 1000 series)
- 1/4" AR200 Side Walls
- 5/8" AR200 Lower Screw Flighting
- Front Center Door With 8 Ft. (1200T-10') Hydraulic Driven Chain Conveyor, Right Or Left Discharge (Specify On Order)
 - Discharge Height For Model 700T Is Approx. 22", Approx. 29" For Model 900T, Approx. 32' For Models 1000T/1200T And Approx. 34" For Model 1400T
- 1400T Fluid Coupling For Easy Start Up
- 1000T/1200T/1400T Stainless Steel Lined Auger Outer Edge And Ultra Wear Kicker Plates
- Heavy Duty Hitch Jack
- 4 point DG Electronic Scale system with Remote Port and 10 Recipe Programming Capability.
- 12 Volt Battery
- Model 600T/ 700T (2) 40x14.5x19 A/C tires (14,000 lbs)*
Model 900T (4) 11R/22.5, 16 Ply Truck tires With Budd Wheels And HD Axle (24,000 lbs.)*
- Model 1000T/1200T (2) 700/50-22.5 Floatation (40,000 lbs.)*
- Model 1400T (8) 275/70R 22.5 Tires With Walking Beam Tandem Axle (40,000 Lbs.)*
- Tub Mounted Hydraulic Interference Knife Assemblies (2)



* Maximum Payload At A Speed Of Less Than 5 mph