

Model Specifications

For the

600T, 700T, 900T, 1000T, 1200T & 1400T

Truck Mounts



Model 600T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	10,100 lbs.	4,591 kg.
- Height*	82 in.	209 cm
- W/10" Extension	92 in.	234 cm
- Overall Width**	102 in.	259 cm
- Min. HP Req.	210	
- Capacity W/10" Extension (cu. ft.)	641 cu. ft.	18.2 cu.m
- Capacity Struck Level	549 cu. ft.	15.5 cu.m

Model 700T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	10,100 lbs.	4,591 kg.
- Height*	90 in.	229 cm
- W/10" Extension	100 in.	254 cm
- Overall Width**	102 in.	259 cm
- Min. HP Req.	210	
- Capacity W/10" Extension (cu. ft.)	649 cu. ft.	18.4 cu.m
- Capacity Struck Level	568 cu. ft.	16.1 cu.m

Model 900T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	14,700 lbs.	6,682 kg.
- Height*	90 in.	229 cm
- W/10" Extension	100 in.	254 cm
- Overall Width**	120 in.	305 cm
- Min. HP Req.	250	
- Capacity W/10" Extension (cu. ft.)	849 cu. ft.	24.1 cu.m
- Capacity Struck Level	739 cu. ft.	20.9 cu.m

Model 1000T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	18,900 lbs.	8,591 kg.
- Height*	82 in.	208 cm
- W/10" Extension	92 in.	233 cm
- Overall Width**	102 in.	259 cm
- Min. HP Req.	350	
- Capacity W/10" Extension	906 cu.ft.	25.7 cu.m
- Capacity Struck Level (cu. ft.)	789 cu.ft.	22.3 cu.m

Model 1200T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	19,300 lbs.	8,773 kg.
- Height*	92 in.	233 cm
- W/10" Extension	102 in.	258 cm
- Overall Width**	102 in.	259 cm
- Min. HP Req.*	350	
- Capacity W/10" Extension	1038 cu.ft.	29.4 cu.m
- Capacity Struck Level (cu. ft.)	917 cu.ft.	26.0 cu.m

Model 1400T Truck Mount	imperial	metric
- Empty Weight (Processor Only)	21,500 lbs.	9,773 kg.
- Height*	97 in.	247 cm
- W/10" Extension	107 in.	272 cm
- Overall Width**	120 in.	305 cm
- Min. HP Req.	400	
- Capacity W/10" Extension (cu. ft.)	1312 cu. ft.	37.2 cu.m
- Capacity Struck Level	1157 cu. ft.	32.8 cu.m

Additional information

* Height of tub only. Add to truck frame height for overall height.

** Overall width and length dependent on style of truck, conveyor/discharge and options ordered.

Due to continuing improvements in the design and manufacturing of equipment, specifications and technical data are subject to change without incurring any obligation on goods purchased.

Models 600T, 700T, 900T, 1000T, 1200T & 1400T Truck Mounts

STANDARD EQUIPMENT

- 100% Hydrostatic Drive System
- Electronic Engine Shut Down For Hydraulic System Protection
- Control Valves
- Large Capacity Hydraulic Oil Reservoir
- Heavy-Duty Oil Cooling System With Automatic Fans
- Control Console For Scale And Variable Auger Control Levers
- Two Patented Freestanding Vertical Mixing Augers
- Stainless Steel Lined, Outer Leading Edge & Ultra Wear Kicker Plates
- Replaceable Cutting Blades (10)
- AR200 Steel Backing Plates
- Front Center Discharge Door
- Viewing Platform
- 8 ft. Flat Variable Speed Hydraulic Driven Chain Discharge Conveyor With Hydraulic Extender
- 4 Point DG Electronic Scale System with 10 Recipe Programming Capability and Remote readout and mirror mount remote readout.
- Heavy-Duty Tubular Steel Bolsters
- 3/4" M/S Floor on TM600T/ TM700T/TM900T (1" on all 1000 series)
- 1/4" AR200 Side Walls
- 5/8" AR200 Lower Screw Flighting
- Tub Mounted Hydraulic Interference Knife Assemblies (2)

