

# Model Specifications

## for the 600T, 700T, 900T, 1000T, 1200T, & 1400T

### PTO Drive Stationary Processors (Twin Auger)



<b>Model 600T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	12,360 lbs.	5,618 kg.
- Overall Height with 6" Pedestal**	104 in.	264 cm
- Overall Height with 24" Pedestal**	122 in.	310 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	102 in.	259 cm
- Overall Length	253 in.	617 cm
- Min. HP Req. (electric)	100	
- Capacity W/10" Extension (cu. ft.)	641 cu. ft.	18.2 cu. m
- Capacity Struck Level	549 cu. ft.	15.5 cu. m

<b>Model 700T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	12,360 lbs.	5,618 kg.
- Overall Height with 6" Pedestal**	109 in.	277 cm
- Overall Height with 24" Pedestal**	127 in.	323 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	102 in.	259 cm
- Overall Length	239 in.	607 cm
- Min. HP Req. (electric)	100	
- Capacity W/10" Extension (cu. ft.)	649 cu. ft.	18.4 cu. m
- Capacity Struck Level	568 cu. ft.	16.1 cu. m

<b>Model 900T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	14,155 lbs.	6,434 kg.
- Overall Height with 6" Pedestal**	108 in.	274 cm
- Overall Height with 24" Pedestal**	126 in.	320 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	121 in.	307 cm
- Overall Length	275 in.	698 cm
- Min. HP Req. (electric)	125	
- Capacity W/10" Extension (cu. ft.)	849 cu. ft.	24.1 cu. m
- Capacity Struck Level	739 cu. ft.	20.9 cu. m

<b>Model 1000T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	18,420 lbs.	8,373 kg.
- Overall Height with 6" Pedestal**	90 in.	229 cm
- Overall Height with 24" Pedestal**	108 in.	274 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	102 in.	259 cm
- Overall Length	299 in.	759 cm
- Min. HP Req. (electric)	200	
- Capacity W/10" Extension	906 cu.ft.	25.7 cu.m
- Capacity Struck Level (cu. ft.)	789 cu.ft.	22.3 cu.m

<b>Model 1200T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	19,920 lbs.	9,055 kg.
- Overall Height with 6" Pedestal**	100 in.	254 cm
- Overall Height with 24" Pedestal**	118 in.	300 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	121 in.	307 cm
- Overall Length	304 in.	772 cm
- Min. HP Req. (electric)	200	
- Capacity W/10" Extension	1072 cu.ft.	30.4 cu.m
- Capacity Struck Level (cu. ft.)	933 cu.ft.	26.4 cu.m

<b>Model 1400T ST(rear door)</b>	<b>imperial</b>	<b>metric</b>
- Empty Weight*	21,020 lbs.	9,555 kg.
- Overall Height with 6" Pedestal**	111 in.	282 cm
- Overall Height with 24" Pedestal**	129 in.	328 cm
- W/10" Extension	+10 in.	+25.4 cm
- Overall Width	121 in.	307 cm
- Overall Length	327 in.	831 cm

### All Above Models

\* Weight is for processor and mount package and does not include the weight of switch gear and electric motor.

\*\* Overall height is dependent on fixed chute minimum height requirements.

Due to continuing improvements in the design and manufacturing of equipment, specifications and technical data are subject to change without incurring any obligations on goods purchased.

# Models 600T/1400T PTO Drive Stationary Processors

## STANDARD EQUIPMENT

- (2) Patented Free Standing Vertical Auger
- (2) Heavy Duty Planetary Drive
- (10) Replaceable Cutting Blades
- AR200 Steel Backing Plates
- ¾" M/S Floor 600T, 900T (1" on all 1000 series)
- ¼" AR200 Side Walls
- 5/8" AR200 Lower Auger Flighting
- Rear door with Fixed Chute
- Viewing Platform
- 4 Point DG Scale System with Scale Console and Remote Readout on tub
- Fluid Coupling
- H/D Tubular Steel Frame and Motor Mount System
- 2 GPM Power Pack for Door Operation
- Stainless Steel Lined Auger Outer Edge and Ultra Wear Kicker Plates
- Tub Mounted Hydraulic Interference Knife Assemblies (2)



**NOTE:** Standard equipment specifications are for electric motor drive models. Contact factory for specifications for diesel motor drive models.